	Page: 1
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil 3657	Version: 3.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : SynPower™ 5W30
Synthetic Motor Oil

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification


No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components


Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 20.00 - < 30.00
Mineral Oil		Asp. Tox. 1; H304	>= 1.00 - < 10.00
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3	Skin Corr/Irr 3; H316 Aquatic Chronic 4; H413	>= 1.00 - < 10.00

	Page: 2
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil 3657	Version: 3.0

Alkyl alcohol triester with boric acid (H3BO3)		Skin Sens. 1B; H317 Aquatic Acute 2; H401	>= 0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

General advice	: No hazards which require special first aid measures.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea)

	Page: 3
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil 3657	Version: 3.0

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES


- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NO_x)
- Specific extinguishing methods : Standard procedure for chemical fires.
- Product is compatible with standard fire-fighting agents.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

		Page: 4
SAFETY DATA SHEET		Revision Date: 01/08/2018
		Print Date: 2/19/2018
		SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil		Version: 3.0
3657		

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
------------	---------	----------------------------------	---	-------

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : mild


Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 330 °C (1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas


Flash point : > 199 °C Method: Cleveland open cup

	Page: 5
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil	Version: 3.0
3657	

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8473 g/cm3
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 63.17 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

	Page: 6
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil 3657	Version: 3.0

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: Rabbit
Result: Mild skin irritation
Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.


Components:

PETROLEUM DISTILLATES:

Result: No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: Rabbit

	Page: 7
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil	Version: 3.0
3657	

Result: **Slight, transient irritation**
Remarks: **Information given is based on data obtained from similar substances.**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

Method: **OECD Test Guideline 406**

Alkyl alcohol triester with boric acid (H3BO3):

Assessment: **The product is a skin sensitiser, sub-category 1B.**

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: **Ames test**

Test species: **Salmonella typhimurium**

Metabolic activation: **with and without metabolic activation**

Result: **negative**

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Mineral Oil:

SAFETY DATA SHEET

Revision Date: 01/08/2018

Print Date: 2/19/2018

SDS Number: R0252918

SynPower™ 5W30 Synthetic Motor Oil

Version: 3.0

3657

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

PETROLEUM DISTILLATES:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

Alkyl alcohol triester with boric acid (H3BO3):

Toxicity to fish	: LC50 (Fish): 1.3 mg/l Exposure time: 96 h
Toxicity to daphnia and other	: EC50 (Daphnia magna (Water flea)): 2.6 mg/l

SAFETY DATA SHEET

Revision Date: 01/08/2018

Print Date: 2/19/2018

SDS Number: R0252918

SynPower™ 5W30 Synthetic Motor Oil

Version: 3.0

3657

aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EC50 (Scenedesmus quadricauda (Green algae)): 9 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.9 mg/l
Exposure time: 21 d

No data available

Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Alkyl alcohol triester with boric acid (H3BO3):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-octanol/water : log Pow: > 7.5

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:


SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

		Page: 10
SAFETY DATA SHEET		Revision Date: 01/08/2018
		Print Date: 2/19/2018
		SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil		Version: 3.0
3657		

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

UN_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL


AICS : Not in compliance with the inventory

ENCS : Contact your sales representative for additional information.

KECI : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)

PICCS : Not in compliance with the inventory

	Page: 11
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil	Version: 3.0
3657	

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/08/2018

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H401	Toxic to aquatic life.
H413	May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).


CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

	Page: 12
SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 2/19/2018
	SDS Number: R0252918
SynPower™ 5W30 Synthetic Motor Oil	Version: 3.0
3657	

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology

Children's Hospital Clinic, Faculty of Medicine

University of São Paulo.

BR OEL : Occupational Exposure Limit (Brazil)

UY OEL : Occupational Exposure Limit (Uruguay)

PY OEL : Occupational Exposure Limit (Paraguay)